

HDMI 1.4 to DP1.2A CONVERTER

P4K2-HD



OVERVIEW

P4K2-HD is a converter to convert the HDMI1.4 signal to DP1.2 A for output. It support resoluion up to 3840 x 2160 @30Hz.

FEATURES

- Plug & play
- HDMI speed up to 2.97 GbPs
- HDCP 1.1 compliant
- DisplayPort output supports link rate RBR (1.62Gbps)/ HBR (2.7Gbps) / HBR2 (5.4 Gbps)
- Resolution up to 3840 x 2160@30Hz
- Low power consumption, no external power required
- EDID pass through



SPECIFICATION

MODEL NO.	P4K2-HD
INPUT INTERFACE	1 x HDMI Type A female Resolution 3840 x 2160@30Hz, 1920 x 1080 p @120Hz
OUTPUT INTERFACE	1 x DisplayPort male Resolution 1920 x 1080Pp @120Hz 24 bit, 1920 x 1200p @60Hz 24 bit, 3840 x 2160@30Hz 24 bit
AUDIO	7.1 digital up to 192kHz sampling rate
POWER	DC 12V/2A, locking barrel connector
ENVIRONMENT	Operating temperature -20~85°C Working humidity 20~95% RH non-condensing
DIMENSION	40 x 15 x 45 mm (W x H x D), cable length 95mm
WEIGHT	25 G

FRONT & BACK VIEW

